



QINGDAO PEAK SEA UNIVERSE INTERNATIONAL TRADE CO., LTD

www.peaksea.cn

sales@peaksea.com.cn peaksea@163.com



Based on German technology and improvements from industrial peers, Peak Sea high speed quilting machine is about 30% more efficient than traditional needle bar quilting machine, we have recently launched our new model for 2018, we welcome you to contact us to get detailed specifications.

Qingdao Peak Sea has achieved ISO9001 certification on manufacturing quilting machines, and our quilting machine line includes many kinds modles & specifications to suit your requirement, we keep a strong focus on stable quality , high production efficiency and best service. Our experienced technical team will continue to strive to provide best solutions to meet your need. you will find us as a good partner in business. We look forward to your inquiries.

高速绗缝机与传统绗缝机相比具有以下优点：

Compared with traditional quilting machine, Reid high-speed quilting machine possesses the following advantages:

- 1、不再使用针杆，采用摇臂式传动，速度能达到800RPM，生产效率较传统绗缝机能提高30%以上。
- 2、大量采用进口免加油轴承和直线导轨，机器又干净又快。
- 3、机器横梁使用更粗的方管，更牢靠的底座，并且在很多地方增加了加强筋，机器即使在高速运转都很稳定。
- 4、在外观设计上运用了色彩学搭配，并且大量采用喷砂和喷塑，机器看上去非常靓丽养眼，给人高档的视觉享受。
- 5、电脑控制部分可以根据您的要求选择工控主机和我公司最新研发的PLC+触摸屏控制。

- 1、Driven by rocker arm with no needle bar, realizing a maximum 800RPM speed and 30% higher efficiency than that of the traditional quilting machine;
- 2、Increasingly adopting imported bearing free of oil and liner guide rail to facilitate a clean and spry machine;
- 3、Adopting thicker square tube at the cross beam and more reliable base, and adding reinforcing ribs at many parts so that the machine could keep stable even at high-speed operation;
- 4、Appearance design integrating color collocation elements, together with process of massive abrasive blasting and powder painting gifting you a beautiful and gorgeous feeling;
- 5、Two computer control choices upon your requirement: IPC or our newly released PLC+Touch Panel control (lower price).

参数 (单位mm) Parameter(Unit mm)	RDS-64-2C/YXG-64-3C	RDS-76-2C/YXG-76-3C	RDS-94-2C/YXG-94-3C	RDS-128-2C/YXG-128-3C
主机尺寸Size:L*W*H	3900*1200*1700	4500*1200*1700	5000*1200*1700	6100*1200*1700
全机重量Weight	3100kg	3450kg	4000kg	4800kg
绗缝宽度Quilting width	1700	2000	2450	3200
针排距Needle bar space	2C 76.2(3*)3B 152.4(3* +3*)	2C 76.2(3*)3B 152.4(3* +3*)	2C 76.2(3*)3B 152.4(3* +3*)	2C 76.2(3*)3B 152.4(3* +3*)
针距Needle space	25.4	25.4	25.4	25.4
X行程X-axis movement	254	254	254	254
绗缝厚度Quilting thickness	≤50	≤50	≤50	≤50
步长Stich	2-6	2-6	2-6	2-6
生产速度Output	0-195m/h	0-195m/h	0-195m/h	0-195m/h
机针型号Needle type	#16. #19	#16. #19	#16. #19	#16. #19
主轴转速Rolling speed	500-800r/min	500-800r/min	500-800r/min	500-800r/min
电压(AC) Rated voltage(AC)	38V/50HZ 220V/60HZ	38V/50HZ 220V/60HZ	38V/50HZ 220V/60HZ	38V/50HZ 220V/60HZ
功率Power	3KW	3.2KW	3.5KW	4KW



QINGDAO PEAK SEA UNIVERSE INTERNATIONAL TRADE CO., LTD

www.peaksea.cn

TEL: 0086 15376779381